



**FEL-PRO INSTALLATION TIPS**

**IMPORTANT:**

Use the O-ring supplied to fabricate new front main cap seals.

Cut 2 sections of the O-ring to approximately 1.125 inches in length and lay in the cap groove.

© 2007 Federal Mogul Corporation  
Form No. I-2104 (09/13)

Printed in U.S.A.



**FEL-PRO INSTALLATION TIPS**

**IMPORTANT:**

Use the O-ring supplied to fabricate new front main cap seals.

Cut 2 sections of the O-ring to approximately 1.125 inches in length and lay in the cap groove.

© 2007 Federal Mogul Corporation  
Form No. I-2104 (09/13)

Printed in U.S.A.



**FEL-PRO INSTALLATION TIPS**

**IMPORTANT:**

Use the O-ring supplied to fabricate new front main cap seals.

Cut 2 sections of the O-ring to approximately 1.125 inches in length and lay in the cap groove.

© 2007 Federal Mogul Corporation  
Form No. I-2104 (09/13)

Printed in U.S.A.



**FEL-PRO INSTALLATION TIPS**

**IMPORTANT:**

Use the O-ring supplied to fabricate new front main cap seals.

Cut 2 sections of the O-ring to approximately 1.125 inches in length and lay in the cap groove.

© 2007 Federal Mogul Corporation  
Form No. I-2104 (09/13)

Printed in U.S.A.



**FEL-PRO INSTALLATION TIPS**

**IMPORTANT:**

Use the O-ring supplied to fabricate new front main cap seals.

Cut 2 sections of the O-ring to approximately 1.125 inches in length and lay in the cap groove.

© 2007 Federal Mogul Corporation  
Form No. I-2104 (09/13)

Printed in U.S.A.



**FEL-PRO INSTALLATION TIPS**

**IMPORTANT:**

Use the O-ring supplied to fabricate new front main cap seals.

Cut 2 sections of the O-ring to approximately 1.125 inches in length and lay in the cap groove.

© 2007 Federal Mogul Corporation  
Form No. I-2104 (09/13)

Printed in U.S.A.



**FEL-PRO INSTALLATION TIPS**

**IMPORTANT:**

Use the O-ring supplied to fabricate new front main cap seals.

Cut 2 sections of the O-ring to approximately 1.125 inches in length and lay in the cap groove.

© 2007 Federal Mogul Corporation  
Form No. I-2104 (09/13)

Printed in U.S.A.



**FEL-PRO INSTALLATION TIPS**

**IMPORTANT:**

Use the O-ring supplied to fabricate new front main cap seals.

Cut 2 sections of the O-ring to approximately 1.125 inches in length and lay in the cap groove.

© 2007 Federal Mogul Corporation  
Form No. I-2104 (09/13)

Printed in U.S.A.