SAFETY DATA SHEET

1. Identification

| Product identifier | Deka Battery Cleaner Spray | |
|---------------------------------|-----------------------------|--|
| Other means of identification | | |
| Product Code | 00321 | |
| Recommended use | Battery cleaner | |
| Recommended restrictions | None known. | |
| Manufacturer/Importer/Supplier/ | Distributor information | |
| Manufactured or sold by: | | |
| Company Name | East Penn Manufacturing Co. | |
| Address | 102 Deka Road | |
| | Lyon Station, PA 19536 US | |
| Telephone | | |
| General Information | 610-682-6361 610-682- | |
| Customer Service 24- | 4231 800-424-9300 (US) | |
| Hour Emergency | 703-527-3887 | |
| (CHEMTREC) | (International) | |
| Website | www.dekabatteries.com | |

2. Hazard(s) identification

| Physical hazards | Gases under pressure | Liquefied gas |
|-----------------------|----------------------|---------------|
| Health hazards | Not classified. | |
| Environmental hazards | Not classified. | |
| OSHA defined hazards | Not classified. | |
| Label elements | | |



| Signal word | Warning | |
|---|--|--|
| Hazard statement | Contains gas under pressure; may explode if heated. | |
| Precautionary statement | | |
| Prevention | Do not puncture or incinerate container. Do not expose to heat or store at temperatures above 49°C/120°F. Observe good industrial hygiene practices. | |
| Response | Wash hands after handling. | |
| Storage | Protect from sunlight. Store in a well-ventilated place. Exposure to high temperature may cause can to burst. | |
| Disposal | Dispose of waste and residues in accordance with local authority requirements. | |
| Hazard(s) not otherwise known. classified (HNOC) | None | |
| Supplemental information | None. | |

3. Composition/information on ingredients

Mixtures

| Chemical name | Common name and synonyms | CAS number | % |
|-------------------------|--------------------------|------------|---------|
| water | | 7732-18-5 | 80 - 90 |
| liquefied petroleum gas | | 68476-86-8 | 5 - 10 |
| 2-butoxyethanol | | 111-76-2 | 1 - 3 |

Specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. First-aid measures

| Inhalation | Move to fresh air. Call a physician if symptoms develop or persist. |
|--|--|
| Skin contact | Rinse skin with water/shower. Get medical attention if irritation develops and persists. |
| Eye contact | Rinse with water. Get medical attention if irritation develops and persists. |
| Ingestion | Call a POISON CENTER or doctor/physician. |
| Most important symptoms/effects, acute and delayed | Direct contact with eyes may cause temporary irritation. |
| Indication of immediate medical attention and special treatment needed | Provide general supportive measures and treat symptomatically. |
| General information | Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. |
| 5. Fire-fighting measures | |

| | Suitable extinguishing media | Water fog. Foam. Dry chemical powder. Carbon dioxide (CO2). |
|--------------------------------|---|--|
| | Unsuitable extinguishing media | Do not use water jet as an extinguisher, as this will spread the fire. |
| | Specific hazards arising from the chemical | Pressurized container may rupture when exposed to heat or flame. During fire, gases hazardous to health may be formed. |
| | Special protective equipment and precautions for firefighters | Self-contained breathing apparatus and full protective clothing must be worn in case of fire. |
| | Fire fighting equipment/instructions | In case of fire: Stop leak if safe to do so. Move containers from fire area if you can do so without risk. Containers should be cooled with water to prevent vapor pressure build up. |
| | General fire hazards | Contents under pressure. Pressurized container may rupture when exposed to heat or flame. |
| 6. Accidental release measures | | ures |
| | Personal precautions, protective equipment and emergency procedures | Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Keep out of low areas. Many gases are heavier than air and will spread along ground and collect in low or confined areas (sewers, basements, tanks). Wear appropriate protective equipment and clothing |

| protective equipment and emergency procedures | of low areas. Many gases are heavier than air and will spread along ground and collect in low or confined areas (sewers, basements, tanks). Wear appropriate protective equipment and clothing during clean-up. Emergency personnel need self-contained breathing equipment. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS. |
|--|--|
| Methods and materials for containment and cleaning up | Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. This product is miscible in water. Stop the flow of material, if this is without risk. Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination. For waste disposal, see section 13 of the SDS. |
| Environmental precautions | Avoid discharge into drains, water courses or onto the ground. |
| 7. Handling and storage | |
| Precautions for safe handling Pressurized container: Do not pierce or burn, even after use. Do not use if spray button or defective. Do not spray on a naked flame or any other incandescent material. Do not while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grin expose containers to heat, flame, sparks, or other sources of ignition. Use caution arour energized equipment. The metal container will conduct electricity if it contacts a live sou may result in injury to the user from electrical shock and/or flash fire. Do not get in eyes, or on clothing. Avoid prolonged exposure. Use only in well-ventilated areas. Wear appro- personal protective equipment. Observe good industrial hygiene practices. For product i instructions, see the product label. | |
| Conditions for safe storage, | Level 1 Aerosol. |
| including any incompatibilities | Contents under pressure. Do not expose to heat or store at temperatures above 120°F/49°C as can may burst. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. Store in a well-ventilated place. Stored containers should be periodically checked for general condition and leakage. Store away from incompatible materials (see Section 10 of the SDS). |

8. Exposure controls/personal protection

Occupational exposure limits

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit. At this time, the other constituents have no known exposure limits.

| US. OSHA Table Z-1 Lin Components | | nts (29 CFR 1910 /pe | 1000) Val | lue |
|--|--|---|---------------------------------|---|
| 2-butoxyethanol (CAS 111-76-2) | PE | EL | 24 | 0 mg/m3 |
| | | | 50 | ppm |
| US. ACGIH Threshold L | | | | |
| Components | | ире | - | alue |
| 2-butoxyethanol (CAS 111-76-2) | Tν | VA | 20 | ppm |
| US. NIOSH: Pocket Guid Components | | ls /pe | Va | alue |
| 2-butoxyethanol (CAS 111-76-2) | T۷ | VA | 24 | mg/m3 |
| | | | 5 p | pm |
| Biological limit values | | | | |
| ACGIH Biological Expose Components | sure Indices Value | Determinant | Specimen | Sampling Time |
| 2-butoxyethanol (CAS 111-76-2) | 200 mg/g | Butoxyacetic acid (BAA), with hydrol | Creatinine in urine ysis | * |
| * - For sampling details, p | lease see the source d | ocument. | | |
| Exposure guidelines | | | | |
| US - California OELs: S | kin designation | | | |
| 2-butoxyethanol (CA US - Minnesota Haz Sub | | | be absorbed throu | gh the skin. |
| 2-butoxyethanol (CA US - Tennessee OELs: \$ | | Skii | n designation applie | S. |
| 2-butoxyethanol (CA US NIOSH Pocket Guide | | | n be absorbed throu n | gh the skin. |
| 2-butoxyethanol (CA US. OSHA Table Z-1 Lin | | | be absorbed throu 1000) | gh the skin. |
| 2-butoxyethanol (CA | | - | be absorbed throu | gh the skin. |
| Appropriate engineering | controls should ventilation, or other enginee | be matched to co ring controls to ma | intain airborne leve | nour) should be used. Ventilation rates ole, use process enclosures, local exhaust ils below recommended exposure limits. If rborne levels to an acceptable level. |
| Eye/face protection | ndividual protection r Wear safety glas | neasures, such as ses with side shiel | | ve equipment |
| Skin protection Hand protection | | | | |
| Other | • | gloves such as: Nit | rile. | |
| Respiratory protection | Wear suitable pr | - | | |
| Thermal hazards | NIOSH-approved | d cartridge respirate atus in confined spa | or with an organic va | xceeds the applicable exposure limits, use a apor cartridge. Use a self-contained encies. Air monitoring is needed to determine |
| | Wear appropriate | e thermal protective | e clothing, when neo | cessary. |
| General hygiene considerations | after handling the | e material and befo | | onal hygiene measures, such as washing and/or smoking. Routinely wash work ants. |

9. Physical and chemical properties

Appearance

| | Physical state | Liquid. |
|---|---|----------------------------|
| | Form | Aerosol. |
| | Color | Clear. |
| С | Ddor | Odorless. |
| С | Odor threshold | Not available. |
| р | Н | 8.5 |
| N | lelting point/freezing point | -103 °F (-75 °C) estimated |
| | nitial boiling point and boiling : ange | 212 °F (100 °C) estimated |
| F | lash point | None (Closed Cup) |
| E | evaporation rate | Slow. |
| F | lammability (solid, gas) | Not available. |
| U | Ipper/lower flammability or exp | olosive limits |
| | Flammability limit - lower (%) | 1.3 % estimated |
| | Flammability limit - upper (%) | 10.6 % estimated |
| ۷ | apor pressure | 268.5 hPa estimated |
| ۷ | apor density | > 1 (air = 1) |
| R | Relative density | 1.04 |
| S | Solubility(ies) | |
| | Solubility (water) | Soluble. |
| - | Partition coefficient n-octanol/water) | Not available. |
| A | uto-ignition temperature | 446 °F (230 °C) estimated |
| D | Decomposition temperature | Not available. |
| Ρ | Percent volatile | 94.3 % estimated |
| | | |

10. Stability and reactivity

| Reactivity | The product is stable and non-reactive under normal conditions of use, storage and transport. |
|---------------------------------------|---|
| Chemical stability | Material is stable under normal conditions. |
| Possibility of hazardous reactions | No dangerous reaction known under conditions of normal use. |
| Conditions to avoid | Heat, flames and sparks. Contact with incompatible materials. |
| Incompatible materials | Strong oxidizing agents. |
| Hazardous decomposition products | Carbon oxides. Aldehydes. Ketones. Organic acids. |

11. Toxicological information

Information on likely routes of exposure

| Inhalation | Prolonged inhalation may be harmful. | |
|--|--|--|
| Skin contact | 2-Butoxy ethanol may be absorbed through the skin in toxic amounts if contact is repeated and prolonged. These effects have not been observed in humans. | |
| Eye contact | Direct contact with eyes may cause temporary irritation. | |
| Ingestion | Expected to be a low ingestion hazard. | |
| Symptoms related to the physical, chemical and toxicological characteristics | Direct contact with eyes may cause temporary irritation. | |
| Information on toxicological effe | ects | |
| Acute toxicity | Not known. | |

| Components | Species | Test Results |
|--|--|--|
| 2-butoxyethanol (CAS 111-76-2) | | |
| Acute | | |
| Oral | | |
| LD50 | Rat | 1300 mg/kg |
| Skin corrosion/irritation | Prolonged skin contact may | cause temporary irritation. |
| Serious eye damage/eye irritation | Direct contact with eyes may | y cause temporary irritation. |
| Respiratory or skin sensitization | า | |
| Respiratory sensitization | Not a respiratory sensitizer. | |
| Skin sensitization | This product is not expected | to cause skin sensitization. |
| Germ cell mutagenicity | No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic. | |
| Carcinogenicity | Not classifiable as to carcinogenicity to humans. | |
| IARC Monographs. Overall Evaluation of Carcinogenicity | | |
| 2-butoxyethanol (CAS 111-76-2) 3 Not classifiable as to carcinogenicity to humans. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1052) | | |
| Not regulated. | ogram (NTP) Report on Carci | nodens |
| Not listed. | | |
| Reproductive toxicity | This product is not expected | to cause reproductive or developmental effects. |
| Specific target organ toxicity - single exposure | Not classified. | |
| Specific target organ toxicity - repeated exposure | Not classified. | |
| Aspiration hazard | Not an aspiration hazard. | |
| Chronic effects | May be harmful if absorbed | through skin. Prolonged inhalation may be harmful. |
| | | sorbed through the skin in toxic amounts if contact is repeated and ave not been observed in humans. |

12. Ecological information

| Ecotoxicity | The product is not classified as environmentally hazardous. However, this does not exclude the |
|-------------|---|
| | possibility that large or frequent spills can have a harmful or damaging effect on the environment. |

| Components | | Species | Test Results |
|---|---|---|-------------------------|
| 2-butoxyethanol (CAS 111-7 | 6-2) | | |
| Aquatic | | | |
| Acute | | | |
| Crustacea | EC50 | Water flea (Daphnia magna) | 1550 mg/l, 48 hours |
| Fish | LC50 | Rainbow trout,donaldson trout (Oncorhynchus mykiss) | >= 1000 mg/l, 96 hours |
| ersistence and degradability oaccumulative potential | No data is | s available on the degradability of any ingre | edients in the mixture. |
| Partition coefficient n-octa | nol / water (| 0, | |
| 2-butoxyethanol | | 0.81, log Pow | |
| obility in soil | No data a | vailable. | |
| her adverse effects | No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component. | | |

13. Disposal considerations

| Disposal instructions | The dispensed liquid product is not a RCRA hazardous waste (See 40 CFR Part 261.20 - 261.33). Consult authorities before disposal. Contents under pressure. Do not puncture, incinerate or crush. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in accordance with local/regional/national regulations. |
|-----------------------|---|

Hazardous waste codeNot regulated.Contaminated packagingEmpty containers should be taken to an approved waste handling site for recycling or disposal.
Since emptied containers may retain product residue, follow label warnings even after container is

emptied. Do not re-use empty containers.

14. Transport information

| DOT | | |
|--|---|--|
| UN number | UN1950 | |
| UN proper shipping name | Aerosols, non-flammable, Limited Quantity | |
| Transport hazard class(es) | | |
| Class | 2.2 | |
| Subsidiary risk | | |
| Label(s) | 2.2 | |
| Packing group | Not applicable. | |
| | r Read safety instructions, SDS and emergency procedures before handling. | |
| Packaging exceptions | 306 | |
| Packaging non bulk | None | |
| Packaging bulk | None | |
| IATA | | |
| UN number | UN1950 | |
| UN proper shipping name | Aerosols, non-flammable, Limited Quantity | |
| Transport hazard class(es) | | |
| Class | 2.2 | |
| Subsidiary risk | - | |
| Packing group | Not applicable. | |
| ERG Code | 2L | |
| Special precautions for use | r Read safety instructions, SDS and emergency procedures before handling. | |
| Other information | | |
| Passenger and cargo aircraft | Allowed with restrictions. | |
| Cargo aircraft only | Allowed with restrictions. | |
| IMDG | | |
| UN number | UN1950 | |
| UN proper shipping name | AEROSOLS, Limited Quantity | |
| Transport hazard class(es) | | |
| Class | 2 | |
| Subsidiary risk | - | |
| Packing group | Not applicable. | |
| Environmental hazards | | |
| Marine pollutant | No. | |
| EmS | Not available. | |
| Special precautions for use | r Read safety instructions, SDS and emergency procedures before handling. | |
| 15. Regulatory informatio | n | |
| US federal regulations | This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200. | |
| TSCA Section 12(b) Export | Notification (40 CFR 707, Subpt. D) | |
| Not regulated. | | |
| SARA 304 Emergency release notification | | |
| Not regulated. | | |
| OSHA Specifically Regulated Substances (29 CFR 1910.1001-1052) | | |
| Not regulated. | | |
| US EPCRA (SARA Title III) Section 313 - Toxic Chemical: Listed substance | | |
| 2-hutovyethanol (CAS 111-76-2) | | |

2-butoxyethanol (CAS 111-76-2)

2-butoxyethanol (CAS 111-76-2)

CERCLA Hazardous Substance List (40 CFR 302.4)

Listed.

CERCLA Hazardous Substances: Reportable quantity

Not listed.

Spills or releases resulting in the loss of any ingredient at or above its RQ require immediate notification to the National Response Center (800-424-8802) and to your Local Emergency Planning Committee.

| Other federal regulations | | | | |
|--|---|---|---|----------------------|
| Clean Air Act (CAA) Section Not regulated. | n 112 Hazardous Air Po | ollutants (HAPs) List | | |
| Clean Air Act (CAA) Section | n 112(r) Accidental Rel | ease Prevention (40 Cl | FR 68.130) | |
| Not regulated. | | | | |
| Safe Drinking Water Act (SDWA) | Not regulated. | | | |
| Food and Drug Administration (FDA) | Not regulated. | | | |
| Superfund Amendments and Re Classified hazard categories | eauthorization Act of 1 Gas under pressure | 986 (SARA) | | |
| SARA 302 Extremely hazar Not listed. | dous substance | | | |
| | | | | |
| SARA 313 (TRI reporting) Chemical name | | CAS number | % by wt. | |
| 2-butoxyethanol | | 111-76-2 | 1 - 3 | |
| US state regulations | | | | |
| US. New Jersey Worker and | d Community Right-to- | Know Act | | |
| 2-butoxyethanol (CAS 1 US. Massachusetts RTK - S | , | | | |
| 2-butoxyethanol (CAS 1 US. Pennsylvania Worker a | | o-Know Law | | |
| 2-butoxyethanol (CAS 1 US. Rhode Island RTK | 11-76-2) | | | |
| 2-butoxyethanol (CAS 1 | 11-76-2) | | | |
| California Proposition 65 | , | | | |
| | | | | |
| 🔥 WARNING: Ca | ancer and Repr | roductive Harm | www.P65Warnir | igs.ca.gov |
| California Proposition | 65 - CRT· Listed date/(| arcinogenic substance | 0 | |
| 1,4-dioxane (CAS 12 | | Listed: Januar | | |
| ethylene oxide (CAS 75-21-8) | | Listed: July 1, 1987 | | |
| California Proposition | | - | | |
| ethylene oxide (CAS California Proposition | | Listed: Augus Female reproductive to: | | |
| ethylene oxide (CAS California Proposition | | Listed: Februa Aale reproductive toxin | | |
| ethylene oxide (CAS US. California. Candida | | Listed: Augus er Consumer Products | t 7, 2009 • Regulations (Cal. Code Reg | s, tit. 22, 69502.3, |
| subd. (a)) 2-butoxyethanol (CA | | | | |
| liquefied petroleum | gas (CAS 68476-86-8) | | | |
| Volatile organic compounds (V EPA | OC) regulations | | | |
| VOC content (40 CFI 51.100(s)) | R 7.9 % | | | |
| Consumer products (40 CFR 59, Subpt. C) | Not regulated | | | |
| State | | | | |
| Consumer products | Not regulated | | | |
| VOC content (CA) | 7.9 % | | | |
| VOC content (OTC) | 7.9 % | | | |
| | | | | |

International Inventories

| Country(s) or region | Inventory name | On inventory (yes/no)* |
|----------------------------|---|------------------------|
| Australia | Australian Inventory of Chemical Substances (AICS) | Yes |
| Canada | Domestic Substances List (DSL) | Yes |
| Canada | Non-Domestic Substances List (NDSL) | No |
| China | Inventory of Existing Chemical Substances in China (IECSC) | Yes |
| Europe | European Inventory of Existing Commercial Chemical Substances (EINECS) | No |
| Europe | European List of Notified Chemical Substances (ELINCS) | No |
| Japan | Inventory of Existing and New Chemical Substances (ENCS) | No |
| Korea | Existing Chemicals List (ECL) | Yes |
| New Zealand | New Zealand Inventory | Yes |
| Philippines | Philippine Inventory of Chemicals and Chemical Substances (PICCS) | Yes |
| Taiwan | Taiwan Toxic Chemical Substances (TCS) | Yes |
| United States & Puerto Rid | co Toxic Substances Control Act (TSCA) Inventory | Yes |

*A 'Yes' indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A 'No' indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

| , | o |
|---------------------|---|
| Issue date | 1-1-2018 |
| Version # | 01 |
| Further information | Control # 09835(1004673)/530B(1002542) |
| HMIS® ratings | Health: 1 Flammability: 0 Physical hazard: 0 Personal protection: B |
| NFPA ratings | Health: 1 Flammability: 0 Instability: 0 |
| NFPA ratings | |
| Disclaimer | The information contained in this document applies to t be valid for this material if it is used in combination with accurate to the best of our knowledge or obtained from using any product, read all warnings and directions on information contained on this (M)SDS consult your sup- East Penn Manufacturing Company. |
| | |

Revision information

The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. This information is accurate to the best of our knowledge or obtained from sources believed to be accurate. Before using any product, read all warnings and directions on the label. For further clarification of any information contained on this (M)SDS consult your supervisor, a health & safety professional, or East Penn Manufacturing Company. This document has undergone significant changes and should be reviewed in its entirety.